TITLE OF THE INVENTION

ON-VEHICLE ELECTRONIC APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the

5　benefit of priority from the prior Japanese Patent

Application No. 2002-260146, filed September 5, 2002,

the entire contents of which are incorporated herein by

reference.

BACKGROUND OF THE INVENTION

10　　1.　Field of the Invention

The present invention relates to an on-vehicle

electronic apparatus and, more particularly, to a car

navigation apparatus that uses a wireless LAN.

2.　Description of the Related Art

15　　In recent years, an automobile which comprises an

obstacle detection/warning device has been proposed.

As an example of such automobile, ultrasonic sensors

are provided to the front and rear portions of a

vehicle so as to detect the distances between vehicles

20　and to detect any obstacle.

Each ultrasonic sensor radiates ultrasonic pulses,

and receives a wave reflected by any obstacle, thereby

detecting an obstacle.　Furthermore, by measuring the

time required until the reflected wave is received, the

25　distance to the obstacle can be measured.

Upon detection of an obstacle, an audible warning

is generated or a warning dialog is displayed to issue

a warning to the driver (e.g., see Jpn. Pat. Appln. KOKAI Publication No. 2000-330637).

On the other hand, a car navigation system that mounts a GPS (Global Positioning System) has been developed. Such car navigation system can display information associated with car navigation such as a travel history or the like on a map, and can download and update map information from a server connected to the Internet using a line of a portable phone attached to the car navigation system.

The user can reach a destination by referring to information associated with car navigation such as a travel history or the like on the map, which is displayed on the display screen of the car navigation system (e.g., see Jpn. Pat. Appln. KOKAI Publication No. 2002-221430).

However, since the conventional obstacle detection/warning device uses ultrasonic sensors to detect any obstacle, the detection range of such sensor is narrow, and that device cannot effectively avoid collision between vehicles with a sufficient time margin.

The conventional car navigation system can navigate the driver of a vehicle by its navigation function, but cannot effectively avoid collision or the like.

BRIEF SUMMARY OF THE INVENTION

According to the first aspect of the present invention, there is provided an on-vehicle electronic apparatus comprising a wireless communication unit which makes a wireless communication via a wireless LAN, means for acquiring position information and velocity information each indicating positions and velocities of vehicles before and after the self vehicle using the wireless communication unit, means for calculating inter-vehicle distances between the self vehicle, and the vehicles before and after the self vehicle with reference to map information on the basis of the acquired position information and velocity information, and means for taking a collision avoidance measure when the calculated inter-vehicle distances are not more than a predetermined distance, and the velocities of the self vehicle and the vehicles before and after the self vehicle are not less than a predetermined velocity.

According to the second aspect of the present invention, there is provided an on-vehicle electronic apparatus, comprising means for acquiring position information and velocity information each indicating positions and velocities of foremost and rearmost vehicles of a travel group including a self vehicle, and at least one vehicle which is included in the travel group and serves as a wireless transponder using

a wireless LAN of vehicles included in the travel group, means for calculating a length of the travel group using map information on the basis of the acquired position information indicating the positions of the foremost and rearmost vehicles, means for calculating a distance from the foremost vehicle of the travel group to the self vehicle using the map information on the basis of the acquired position information of the foremost vehicle and the acquired position information of the self vehicle, means for calculating a time required until the self vehicle leaves the travel group, on the basis of the acquired velocity information of the respective vehicles and the calculated distance, and means for notifying a driver of the self vehicle of the calculated length of the travel group and the calculated time.

According to the third aspect of the present invention, there is provided an on-vehicle electronic apparatus comprising means for receiving a packet which contains information indicating a position of a transmission destination and information to be transmitted to the transmission destination, from another on-vehicle electronic apparatus, means for, when the packet is received, checking if connection with the transmission destination indicated by the information contained in the packet can be established using a wireless LAN, means for, when the connection

can be established, transmitting the information to be transmitted to the transmission destination, which is contained in the packet, to the transmission destination using the wireless LAN, means for, when the connection cannot be established, acquiring position information and velocity information of vehicles around a self vehicle using the wireless LAN, means for selecting a vehicle closest to the transmission destination on the basis of the acquired position information and velocity information of the vehicles around the self vehicle, and the information which is contained in the packet and indicates the position of the transmission destination, and means for transmitting the packet to the selected vehicle using the wireless LAN.

According to the fourth aspect of the present invention, there is provided an on-vehicle electronic apparatus comprising means for acquiring route information from a plurality of vehicles around a self vehicle using a wireless LAN, means for estimating a route which may be jammed on the basis of the route information acquired from the plurality of vehicles, means for, when the estimated route that may be jammed matches a part of a self route, searching for another route which does not include the matched route, and means for presenting the found route to a driver.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below serve to explain the principles of the invention.

FIG. 1 is a view for explaining the operation of a car navigation apparatus according to the first embodiment of the present invention;

FIG. 2 is a view for explaining a method of selecting position information and velocity information of vehicles before and after the self vehicle;

FIG. 3 is a block diagram showing the arrangement of the car navigation apparatus according to the first embodiment of the present invention;

FIG. 4 is a flow chart for explaining the operation of the car navigation apparatus according to the first embodiment of the present invention;

FIG. 5 is a view for explaining a data structure;

FIG. 6 is a view for explaining the operation of a car navigation apparatus according to the second embodiment of the present invention;

FIG. 7 is a functional block diagram for explaining the functions of a controller 33 in the car navigation apparatus according to the second embodiment

of the present invention;

FIG. 8 is a flow chart for explaining the operation of the car navigation apparatus according to the second embodiment of the present invention;

5   FIG. 9 is a flow chart for explaining the operation of the car navigation apparatus according to the second embodiment of the present invention;

FIG. 10 is flow chart for explaining the operation of the car navigation apparatus according to the second

10   embodiment of the present invention;

FIG. 11 is a view for explaining the operation of a car navigation apparatus according to the third embodiment of the present invention;

FIG. 12 is a functional block diagram for

15   explaining the functions of a controller 33 according to the embodiment of the present invention;

FIG. 13 is a flow chart for explaining the operation of the car navigation apparatus according to the third embodiment of the present invention;

20   FIG. 14 is a functional block diagram for explaining the functions of a controller 33 in a car navigation apparatus according to the fourth embodiment of the present invention;

FIG. 15 shows a display example of a route search

25   result on a screen; and

FIG. 16 is a flow chart for explaining the operation of the car navigation apparatus according to

the fourth embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

A car navigation apparatus according to preferred embodiments of the present invention will be described hereinafter with reference to the accompanying drawings.

<First Embodiment>

FIG. 1 is a view for explaining the operation of a car navigation apparatus according to the first embodiment of the present invention.

In the embodiment of the present invention, navigation apparatuses 2a to 2c mounted on vehicles 1a to 1c avoid any collision using a GPS signal from a satellite 3 and a wireless LAN.

FIG. 3 shows the arrangement of a car navigation apparatus according to the first embodiment of the present invention.

As shown in FIG. 3, a gateway 21 bridges information of a vehicle control system to a bus 26. Also, a portable phone I/F 22 to which a portable phone 23 is attached, a wireless unit 24, and a GPS 25 are connected to the gateway 21, which bridges information from these portable phone I/F 22, wireless unit 24, and GPS 25 to the bus 26.

An LCD (Liquid Crystal Display) 27, a loudspeaker 28, a DVD decoder 29 used to decode a DVD medium 30 that stores map information and the like, an HDD 31

that stores information associated with car navigation,
an input interface 32 of switches, a keyboard, and the
like, and a controller 33 are connected to the bus 26.

The LCD 27 displays information required to carry
out car navigation.

The loudspeaker 28 audibly notifies the user of
information associated with navigation and the like.

The DVD decoder 29 decodes map information or the
like stored in the DVD medium 30.

The HDD 31 stores information associated with car
navigation such as travel history information and the
like, additional information input by the user, and the
like.

The input I/F 32 is an interface for input devices
such as switches, a keyboard, and the like.

The controller 33 controls the overall navigation
apparatus 2, and comprises an information acquisition
module 41, information selection module 42, position
determination module 43, inter-vehicle distance
calculation module 44, and collision avoidance
module 45.

The information acquisition module 41 acquires
position information and velocity information each
indicating positions and velocities of vehicles around
the self vehicle via the wireless unit 24 using the
wireless LAN. Also, the module 41 acquires latitude/
longitude information indicating the position of the

self vehicle and the like using the GPS 25.

The information selection module 42 selects position information and velocity information of vehicles before and after the self vehicle from those around the self vehicle acquired by the information acquisition module 41 with reference to map information. The method of selecting position information and velocity information of vehicles before and after the self vehicle will be described below with reference to FIG. 2.

Referring to FIG. 2, assuming that a vehicle 11b is the self vehicle, and the area of the wireless LAN corresponds to that bounded by the broken line, the self vehicle 11b can wirelessly communicate with vehicles 11a, 11c, and 12a to 12c, and can acquire position information and velocity information from these vehicles 11a, 11c, and 12a to 12c.

With reference to map information, the user can recognize that the vehicles 12a to 12c are traveling along a road different from the self vehicle. Even when these vehicles 12a to 12c are traveling along the identical road, one can recognize on the basis of a velocity vector contained in each velocity information that they are traveling in a direction different from the self vehicle. Hence, it is seen that these vehicles 12a to 12c are not those which are traveling before and after the self vehicle.

On the other hand, one can recognize with reference to the map information that the vehicles 11a and 11c are those which are traveling along the identical road, and based on the velocity information that their velocity vectors point to nearly the same direction. Hence, it becomes apparent that the vehicles 11a and 11b are those which are traveling before and after the self vehicle 11b.

Even if position information and velocity information can be acquired from a vehicle 11d, it is apparent with reference to the position information and map information that the vehicles 11a and 11b are those which are traveling before and after the self vehicle 11b.

The position determination module 43 determines the positions of the vehicles before and after the self vehicle on the map on the basis of the position information of the vehicles before and after the self vehicle acquired by the information acquisition module 41. The module 43 also determines the position on the map on the basis of the position information of the self vehicle.

The inter-vehicle distance calculation module 44 calculates inter-vehicle distances between the self vehicle and the vehicles before and after the self vehicle on the basis of the positions of the self vehicle and the vehicles before and after the self

vehicle, which are determined by the position
determination module 43, with reference to the map
information.

When the inter-vehicle distances calculated by the
inter-vehicle distance calculation module 44 are equal
to or smaller than a predetermined distance and the
velocities of the self vehicle and the vehicles before
and after the self vehicle are equal to or higher than
a predetermined velocity, the collision avoidance
module 45 takes a measure for collision avoidance. The
measure for collision avoidance includes, e.g., display
of a warning message dialog, generation of an audible
warning, deceleration and acceleration of the self
vehicle, and the like.

The operation of the car navigation apparatus
according to the first embodiment of the present
invention will be described below with reference to the
flow chart of FIG. 4.

It is checked in step S1 if an information request
signal from a car navigation apparatus of another
vehicle is received via the wireless LAN. If it is
determined in step S1 that no information request is
received, a request signal of position information and
velocity information is sent to other vehicles using
the wireless LAN (S2).

The data structure of the request signal of such
information has a transmission destination data field

51, transmission source data field 52, command type
field 53, and data field 54, as shown in, e.g., FIG. 5.

The transmission destination data field 51 stores
information indicating a transmission destination.

5　　　When data are to be acquired from all vehicles within
the wireless LAN range of the self vehicle, information
indicating broadcast is stored.

The transmission source data field 52 stores
information indicating the car navigation apparatus

10　　which issued a packet containing those data.

The command type field 53 stores information
indicating the type of command. For example, when the
car navigation apparatus of the self vehicle requests
to acquire position information and velocity

15　　information from that of another vehicle, this field
stores information indicating a command which advises
that apparatus accordingly.

The data field 54 stores data to be sent, e.g.,
position information and velocity information.

20　　　In response to the request, position information
and velocity information of vehicles within the
wireless LAN area are received (S3).

After that, position information and velocity
information of vehicles before and after the self

25　　vehicle are selected from those of the vehicles within
the wireless LAN area received in step S3 on the basis
of the map information and the acquired position

information and velocity information of the respective
vehicles (S4). Furthermore, the positions of the
vehicles before and after the self vehicle on the map
are determined on the basis of their position

5   information (S5). At this time, the position of the
self vehicle on the map is determined with reference to
the map information on the basis of its position
information.

Subsequently, inter-vehicle distances are

10   calculated with reference to the map information on
the basis of the determined positions of the self
vehicle and the vehicles before and after the self
vehicle (S6).

It is then checked if the calculated inter-vehicle

15   distances are equal to or smaller than a predetermined
distance and the velocities of the self vehicle and the
vehicles before and after the self vehicle are equal to
or higher than a predetermined velocity (S7). If it is
determined that these conditions are met, a collision

20   avoidance measure is taken (S8), and the flow returns
to step S1. Also, if it is determined in step S7 that
the conditions are not met, the flow returns to step
S1. Note that the collision avoidance measure
includes, e.g., display of a warning message dialog,

25   generation of an audible warning, deceleration and
acceleration of the self vehicle, and the like.

If it is determined in step S1 that an information

request from another vehicle is received, position information and velocity information of the self vehicle are acquired using the wireless LAN (S9). The acquired position information and velocity information are transmitted to a car navigation apparatus of the other vehicle that issued the information request using the wireless LAN (S10).

Therefore, with the car navigation apparatus according to the embodiment of the present invention, since collision prevention checking is done using the wireless LAN and GPS function without using any sensors, collision between vehicles can be effectively prevented with a sufficient time margin.

Since the wireless LAN is used, an existing car navigation system can be effectively utilized.

<Second Embodiment>

A car navigation apparatus according to another embodiment of the present invention will be described below.

FIG. 6 is a view for explaining the operation of a car navigation apparatus according to the second embodiment of the present invention.

The car navigation apparatus according to this embodiment of the present invention notifies the driver of traffic jam information using a wireless LAN. For example, a case will be examined below wherein vehicles 71-1 to 71-3 are traveling along one road, vehicles

61-1 to 61-17 are traveling along the other road, and the vehicles 61-1 to 61-16 form a travel group caught in a traffic jam, as shown in FIG. 6.

Assuming that a vehicle 61-5 is the self vehicle, it sequentially acquires position information and velocity information of the vehicles 61-1 to 61-16 which form the travel group using the foremost and rearmost vehicles in the wireless LAN area of the self vehicle as transponders (access points), and presents traffic jam information obtained from the acquired information to the driver.

The car navigation apparatus has basically the same arrangement as that shown in FIG. 3, except for functions of a controller. FIG. 7 is a functional block diagram for explaining the functions of the controller 33 in the car navigation apparatus according to the second embodiment of the present invention.

As shown in FIG. 7, the controller 33 comprises an information acquisition module 81, travel group length calculation module 82, distance calculation module 83, time calculation module 84, and traffic jam information presentation module 85.

The information acquisition module 81 acquires position information and velocity information each indicating positions and velocities of vehicles around the self vehicle using the wireless LAN via the wireless unit 24, and also acquires those sent from

vehicles which form a travel group. Furthermore, the module 81 acquires latitude/longitude information indicating the position of the self vehicle and the like using the GPS 25.

5   The travel group length calculation module 82 calculates the length of the travel group with reference to the map information on the basis of the position information of the foremost and rearmost vehicles of those which form the travel group in the

10   information acquired by the information acquisition module 81.

The distance calculation module 83 calculates the distance from the foremost vehicle of the travel group to the self vehicle using map information on the basis

15   of the position information of the foremost vehicle and that of self vehicle in the information acquired by the information acquisition module 81.

The time calculation module 84 calculates the time required until the self vehicle leaves the travel

20   group, on the basis of the velocity information of the respective vehicles acquired by the information acquisition module 81, and the calculated distance.

The traffic jam information presentation module 85 informs the driver of the self vehicle of the length of

25   the travel group calculated by the travel group length calculation module 82, and the time calculated by the time calculation module 84. The traffic jam

information presentation method is not particularly
limited. For example, such information may be
displayed on a screen or may be presented audibly.

5   The operation of the car navigation apparatus
according to the second embodiment of the present
invention will be described below with reference to the
flow charts of FIGS. 8 to 10.

It is initially checked if a packet that contains
position information and velocity information is
10   received from another car navigation apparatus (S21).
If it is determined in step S21 that no packet is
received, it is then checked if an information request
command is received from another car navigation
apparatus (S22).

15   If it is determined in step S22 that no
information request command is received from other car
navigation apparatuses, it is checked if the driver
requests traffic jam information (S23).

If it is determined in step S23 that the driver
20   does not request any traffic jam information, the flow
returns to step S21. On the other hand, if it is
determined in step S23 that the driver requests traffic
jam information, an acquisition request of position
information and velocity information is output to
25   vehicles within the wireless LAN area of the self
vehicle (S24).

Position information and velocity information

which are transmitted from the car navigation apparatuses of surrounding vehicles in response to this acquisition request are acquired (S25). Then, the foremost or rearmost vehicle of the wireless LAN area of the self vehicle is selected based on the acquired information and map information (S26).

A command for acquiring position information and velocity information of the foremost or rearmost vehicle of a travel group including the self vehicle, and at least one vehicle which is included in the travel group and serves as a wireless access point is output to the selected foremost or rearmost vehicle of the wireless LAN area (S27). The flow then returns to step S21.

If it is determined in step S22 that an information request command is received from another car navigation apparatus, an acquisition request of position information and velocity information is output to vehicles within the wireless LAN area of the self vehicle (S28).

Position information and velocity information which are transmitted from the car navigation apparatuses of surrounding vehicles in response to this acquisition request are acquired (S29). Then, a vehicle closest to the vehicle, which issued the command, within the wireless LAN area of the self vehicle is selected based on the acquired information

and map information (S30).

A packet that contains the acquired position information and velocity information of the vehicles around the self vehicle is transmitted to the selected vehicle (S31). This packet has the same data structure as that has been explained in the first embodiment using FIG. 5, and contains transmission destination information, transmission source information, a command type, and the like in addition to data to be transmitted.

It is checked if the self vehicle is the foremost or rearmost vehicle of the travel group (S41). If it is determined in step S41 that the self vehicle is the foremost or rearmost vehicle, the flow returns to step S21.

On the other hand, if it is determined in step S41 that the self vehicle is not the foremost or rearmost vehicle, an acquisition request of position information and velocity information is output to vehicles within the wireless LAN area of the self vehicle using the wireless LAN (S42).

Position information and velocity information which are transmitted from the car navigation apparatuses of surrounding vehicles in response to this acquisition request are acquired (S43). Then, the foremost or rearmost vehicle of the wireless LAN area of the self vehicle is selected based on the acquired

information and map information (S44).

A command for acquiring position information and velocity information of the foremost or rearmost vehicle of the travel group including the self vehicle, and at least one vehicle which is included in the travel group and serves as a wireless access point is output to the selected foremost or rearmost vehicle of the wireless LAN area (S45). The flow then returns to step S21.

If it is determined in step S21 that a packet is received, it is checked if the received packet is addressed to the self vehicle (S32). If it is determined in step S32 that the received packet is not addressed to the self vehicle, the packet is forwarded to a vehicle closest to a transmission destination indicated by transmission destination data contained in that packet (S33). The flow then returns to step S21.

The packet is forwarded by the following method. That is, a packet is received, and position information and velocity information of the vehicles around the self vehicle are acquired. A vehicle closest to the transmission destination is selected on the basis of the acquired position information and velocity information of vehicles around the self vehicle and the map information. The received packet is then forwarded to the selected vehicle.

If it is determined in step S32 that the packet is

addressed to the self vehicle, the packet is received
(S34), and it is checked if position information and
velocity information of the foremost and rearmost
vehicles are received (S51).

If it is determined in step S51 that position
information and velocity information of the foremost
and rearmost vehicles are not received, the flow
returns to step S21. On the other hand, if it is
determined in step S51 that position information and
velocity information of the foremost and rearmost
vehicles are received, the length of the travel group
is calculated using the map information on the basis
of the acquired position information and velocity
information indicating the positions of the foremost
and rearmost vehicles (S52). In addition, the distance
from the foremost vehicle of the travel group to the
self vehicle is calculated using the map information on
the basis of the acquired position information of the
foremost vehicle and that of the self vehicle (S53).

Furthermore, the time required until the self
vehicle leaves the travel group is calculated on the
basis of the distance calculated in step S53 and the
acquired velocity information of respective vehicles in
the travel group (S54). More specifically, this time
is calculated by the following method. The average
velocity of those indicated by the acquired velocity
information of respective vehicles included in the

travel group is calculated, and the calculated distance is divided by the average velocity, thus calculating the time.

The driver is informed of the length of the travel group calculated in step S52, and the time required until the self vehicle leaves the travel group, which is calculated in step S54 (S55). The flow then returns to step S21. In this manner, the driver can recognize the state of a traffic jam.

Therefore, with the car navigation apparatus according to the embodiment of the present invention, when the self vehicle is stuck in traffic, the driver can easily recognize the state of a traffic jam using the wireless LAN, and can drive more comfortably.

<Third Embodiment>

A car navigation apparatus according to the third embodiment of the present invention will be described below.

FIG. 11 is a view for explaining the operation of a car navigation apparatus according to the third embodiment of the present invention. A car navigation apparatus according to the embodiment of the present invention sends information to a transmission destination using a wireless LAN.

For example, upon sending information from a vehicle 102-1 to a home server 104 at home 103 as a transmission destination in FIG. 11, the information is

transferred to the home server 104 as a transmission

destination via vehicles 102-2 to 102-4 serving as

transponders (access points) in turn. Such vehicles

serving as access points are selected based on position

5   information from a satellite 101, which is acquired

using a GPS function, and that selection method is the

same as the method of selecting the vehicle closest to

the transmission destination in the second embodiment.

The home server 104 as the transmission

10   destination delivers information acquired from the

transmission source onto the Internet 106 or the like

via an access point 105.

The car navigation apparatus has basically the

same arrangement as that shown in FIG. 3, except for

15   functions of a controller. FIG. 12 is a functional

block diagram for explaining the functions of the

controller 33 in the car navigation apparatus according

to the embodiment of the present invention.

As shown in FIG. 12, the controller 33 comprises a

20   packet transmission/reception module 111, connection

checking module 112, information acquisition module

113, transmission destination selection module 114, and

transmission request checking module 115.

The packet transmission/reception module 111

25   transmits/receives a packet that contains information

indicating the position of a transmission destination,

and information associated with a transmission source

to/from another on-vehicle electronic apparatus.

The connection checking module 112 checks if connection can be established to a transmission destination indicated by information contained in

5　a packet using a wireless LAN, when the packet transmission/reception module 111 receives the packet.

The information acquisition module 113 acquires position information and velocity information of the self vehicle using a GPS function, and acquires those

10　of vehicles around (within the wireless LAN area of) the self vehicle using the wireless LAN.

The transmission destination selection module 114 selects a vehicle closest to the transmission destination with reference to map information on the

15　basis of the acquired position information and velocity information of vehicles around the self vehicle, and the information which is contained in the packet and indicates the position of a transmission destination.

The transmission request checking module 115

20　checks if the driver issues a packet transmission request.

The operation of the car navigation apparatus according to the third embodiment of the present invention will be described below with reference to the

25　flow chart in FIG. 13.

It is initially checked if the driver issues a packet transmission instruction (S101). If it is

determined in step S101 that the driver does not issue
any transmission instruction, it is checked if a packet
is received from another car navigation apparatus
(S102).

5   This packet has the same data structure as that
has been explained in the first embodiment using
FIG. 5, and contains transmission destination
information, transmission source information, a command
type, and the like in addition to data to be
10   transmitted. The data to be transmitted contains
position information, velocity information, and other
information.

If it is determined in step S102 that no packet is
received, the flow returns to step S101. On the other
15   hand, if it is determined in step S102 that a packet is
received, an attempt is made to establish connection to
a transmission destination indicated by the information
contained in the packet via the wireless LAN (S103).

If wireless connection with the transmission
20   destination cannot be established in step S103,
position information and velocity information of
vehicles around (within the wireless LAN area of) the
self vehicle are acquired (S104), and a vehicle closest
to the transmission destination is selected with
25   reference to map information (S105).

The reason why the velocity information is also
used in selection is to execute a process for, e.g.,

excluding a given vehicle from selection candidates when the difference between the direction of a velocity vector indicated by its velocity information, and that of the velocity vector of the self vehicle is equal to

5   or larger than a predetermined value.

After that, the packet is transmitted to the selected vehicle using the wireless LAN (S106), and the flow then returns to step S101. In this case, information associated with the transmission

10   destination of the packet is recognized by information which indicates the transmission destination and contained in the packet that contains the position information and velocity information acquired in step S104.

15   On the other hand, if it is determined in step S103 that connection with the transmission destination can be established, the packet is transmitted to the transmission destination using the wireless LAN (S107), and the flow returns to step S101.

20   If it is determined in step S101 that the driver issues a packet transmission instruction, a packet which contains information to be sent to a transmission destination is generated (S108). The flow then advances to processes in step S104 and subsequent

25   steps. That is, position information and velocity information of vehicles around (within the wireless LAN area of) the self vehicle are acquired (S104), and a

vehicle closest to the transmission destination is selected with reference to map information (S105). After that, the packet is transmitted to the selected vehicle using the wireless LAN (S106), and the flow returns to step S101.

Note that the information associated with the transmission destination contained in the packet in step S108 may be an image captured by a camera attached to the vehicle. By transmitting such information, if the transmission destination is a server, the image information can be delivered onto the Internet or broadcast, and can be used as traffic information.

In this case, when an IP address unique to the car navigation apparatus of the vehicle as the transmission source is appended to the packet, the transmission source of the image information can be recognized.

Therefore, with the car navigation apparatus according to the embodiment of the present invention, data can be transmitted using the GPS function and wireless LAN, and utilizing vehicles which are present up to a transmission destination as access points.

<Fourth Embodiment>

A car navigation apparatus according to the fourth embodiment of the present invention will be described below.

A car navigation apparatus according to the embodiment of the present invention, which searches for

a route to a destination, and issues an instruction to the driver in correspondence with the current travel position, acquires route information from vehicles around (within the wireless LAN area of) the self

5 vehicle, and searches for another route when a traffic jam in the self route is predicted from the acquired route information.

The car navigation apparatus has basically the same arrangement as that shown in FIG. 3, except for

10 functions of a controller. FIG. 14 is a functional block diagram for explaining the functions of the controller 33 in the car navigation apparatus according to the fourth embodiment of the present invention.

As shown in FIG. 14, the controller 33 comprises a

15 route information acquisition module 121, congested route estimation module 122, match route checking module 123, re-route module 124, and route presentation module 125.

The route information acquisition module 121

20 acquires route information from a plurality of vehicles around the self vehicle using a wireless LAN.

The jammed route estimation module 122 estimates a route that may be jammed on the basis of the route information from a plurality of vehicles acquired by

25 the route information acquisition module 121. More specifically, the jammed route is estimated as follows. The acquired routes from a plurality of vehicles are

searched for overlapping routes, and when the number of overlapping routes is equal to or larger than a predetermined value, it is determined that the overlapping route is jammed.

The match route checking module 123 checks if the jammed route estimated by the jammed route estimation module 122 matches a part of the self route.

The re-route module 124 searches for another route which does not include the matched route when the match route checking module 123 determines a match.

The route presentation module 125 presents the route found by the re-route module 124 to the driver.

The operation of the car navigation apparatus according to the fourth embodiment of the present invention will be described below with reference to the flow chart of FIG. 16.

Initially, route information is acquired from vehicles around the self vehicle using the wireless LAN (S201). The acquisition method of the route information is the same as the method of acquiring position information and velocity information in the first embodiment.

A route that may be jammed is estimated on the basis of the acquired route information from a plurality of vehicles (S202). This route is estimated as described above. That is, the jammed route is estimated as follows. The acquired routes from a

plurality of vehicles are searched for overlapping routes, and when the number of overlapping routes is equal to or larger than a predetermined value, it is determined that the overlapping route is jammed.

It is checked if the jammed route estimated by the jammed route estimation module 122 matches a part of the self route (S203). If they do not match, it is determined that the self route does not include the jammed route, thus ending the process.

However, if it is determined that the two routes match, another route which does not include the matched route is searched for (S204), and the found route is presented to the driver, thus ending the process.

FIG. 15 shows a display example of the route search result on a screen. In FIG. 15, an initial route 133 from a self vehicle 131 to home 132 as a destination is indicated by the broken line. Also, routes 134 of other vehicles are indicated by the solid lines.

Assuming that the initial route 133 of the self vehicle matches a part of the acquired routes 134 of other vehicles, and the number of matches is large enough to predict a traffic jam, rerouting is done. A route 135 is that after rerouting.

Therefore, according to the embodiment of the present invention, in a car navigation apparatus which searches for a route to a destination, and issues an

instruction to the driver in correspondence with the current travel position, a route that does not contain a jammed route can be searched for. Hence, the driver can drive comfortably while beating traffic jams.

5   Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various
10   modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.